



Sierra Premium™ Shake

Sierra Premium™ Shake



Sierra Premium™ Shake Stained Maple



Sierra Premium™ Shake Charcoal Gray



Sierra Premium™ Shake Stained Mahogany

Fiber cement panels will not crack, rot or delaminate.
Fiber cement panels are resistant to fungus and termite infestation.
Fiber cement panels withstand extreme weather conditions.

- Shake available in primed, pre-finished in any color and 8 pre-finished stain colors. (Manufactured by Duckback Products, Inc.- 12-year warranty* on stain finish and 15-year warranty* on paint finish)
- Factory primed and factory sealed on six sides.
- Withstands greater than 150 mph (3 sec. gusts) sustainable winds - ASTM E 330.
- Less breakage during installation with thicker 1/2" panels.
- Longer panels mean less cutting and quicker installation.
- 30-year transferable limited warranty*


**New for
2007**




Caramel



Charcoal Gray



Macadamia




Emerald Wheat



Mahogany




Maple



*Redwood



*Weathered Gray



Primed

Product Specification

Dimensions:	Nominal 9" [h] x 8' [l] Actual 229mm [h] x 2,438mm [l]
Thickness:	Nominal 1/2", Actual 12mm
Weight:	18.6 lbs. per panel / 3.1 lbs. per sq. ft.
Coverage:	6 sq. ft. per panel
Exposed Coverage:	5.17 sq. ft. per panel / 1-1/4" overlap
Manufactured Method:	500 PSI pressed - Non-layered
Autoclaved:	Yes
Sealed:	Six-sides sealed
Finish:	Factory Primed or Factory Pre-finished
Packaging:	4 panels per pack [24 sq. ft.]

Silica Dust Warning. NICHHA products contain crystalline silica (a.k.a. sand, silicon dioxide), which is a common Earth's naturally occurring mineral. Inhalation of crystalline silica into the lungs and repeated exposure, can cause health disorder, such as silicosis, lung cancer, or a potentially death. Whenever drilling, cutting, sawing, sanding or abrading the product, users must observe the following safety practices. 1) Use best work practices to reduce airborne dust concentrations. 2) Work outdoors where feasible, otherwise use mechanical ventilation. 3) Everyone handling NICHHA's product or in the vicinity of others using NICHHA's product must wear safety glasses and properly fitted respirators, prior to handling NICHHA products. We require that users wear a NIOSH/OSHA approved respirator with a rating of N100, P100, or R100 in accordance with applicable government regulations and manufacturer instructions. All employers must comply with the OSHA PEL and ACGIH TLV-TWA. 4) Use a circular saw with dust collector for cutting. The dust collector must be connected to a HEPA vacuum. 5) Do not use compressed air for cleaning dust. 6) Warn others in area. These requirements are designed to help minimize exposure to crystalline silica. We also require that you read all instructions and warnings (including the MSDS) prior to using NICHHA's product. For further information or question, please consult the MSDS or your employer. FAILURE TO ADHERE TO OUR WARNINGS, MSDS, AND OTHER INSTRUCTIONS MAY LEAD TO SERIOUS PERSONAL INJURY OR DEATH.

* Special order colors that require longer lead times

*See Nichiha Warranty for detailed information on terms, conditions and limitations.
 *Note: Printed material may not accurately depict actual product color.

©2007 Nichiha USA, Inc. All rights reserved. Printed in the USA. 6/07 PP N1530
 NIC060607



Nichiha USA, Inc.
 6659 Peachtree Industrial Blvd
 Suite AA, Norcross, GA 30092
 Toll Free: 1.86 NICHHA 1
 (866) 424-4421
 P. (770) 805-9466
 F. (770) 805-9467

www.nichiha.com