



Sierra Premium™ Smooth

Sierra Premium™ Smooth



Sierra Premium™ Smooth Painted



7" Profile
(shown lapped)



8 3/4" Profile
(shown lapped)

Fiber cement panels will not crack, rot or delaminate.
Fiber cement panels are resistant to fungus and termite infestation.
Fiber cement panels withstand extreme weather conditions.

- Smooth available in two profile sizes: 7" and 8 3/4".
- Factory primed and factory sealed on six sides.
- Withstands greater than 150 mph (3 sec. gusts) sustainable winds - ASTM E 330.
- Less breakage during installation with thicker 1/2" panels.
- Longer panels mean less cutting and quicker installation.
- 30-year transferable limited warranty*

Product Specification

Dimensions:	Nominal 7" or 8-3/4"[h] x 10' [l] Actual 178mm or 222mm [h] x 3,030mm [l]
Thickness:	Nominal 1/2 inch, Actual 12mm
Weight:	7" - 18 lbs. per panel / 3.1 lbs. per sq. ft. 8-3/4" - 22.5 lbs. per panel / 3.1 lbs. per sq. ft.
Coverage:	7" - 5.83 sq. ft. per panel 8-3/4" - 7.29 sq. ft. per panel
Exposed Coverage:	7" - 4.79 sq. ft. per panel 8-3/4" - 6.25 sq. ft. per panel [1-1/4" overlap]
Manufactured Method:	500 PSI pressed - Non-layered
Autoclaved:	Yes
Sealed:	Six-sides sealed
Finish:	Factory Primed
Packaging:	4 panels per pack [24 sq. ft.]

Silica Dust Warning. NICHIIHA products contain crystalline silica (a.k.a. sand, silicon dioxide), which is a common Earth's naturally occurring mineral. Inhalation of crystalline silica into the lungs and repeated exposure, can cause health disorder, such as silicosis, lung cancer, or a potentially death. Whenever drilling, cutting, sawing, sanding or abrading the product, users must observe the following safety practices. 1) Use best work practices to reduce airborne dust concentrations. 2) Work outdoors where feasible, otherwise use mechanical ventilation. 3) Everyone handling NICHIIHA's product or in the vicinity of others using NICHIIHA's product must wear safety glasses and properly fitted respirators, prior to handling NICHIIHA products. We require that users wear a NIOSH/OSHA approved respirator with a rating of N100, P100, or R100 in accordance with applicable government regulations and manufacturer instructions. All employers must comply with the OSHA PEL and ACGIH TLV-TWA. 4) Use a circular saw with dust collector for cutting. The dust collector must be connected to a HEPA vacuum. 5) Do not use compressed air for cleaning dust. 6) Warn others in area. These requirements are designed to help minimize exposure to crystalline silica. We also require that you read all instructions and warnings (including the MSDS) prior to using NICHIIHA's product. For further information or question, please consult the MSDS or your employer. FAILURE TO ADHERE TO OUR WARNINGS, MSDS, AND OTHER INSTRUCTIONS MAY LEAD TO SERIOUS PERSONAL INJURY OR DEATH.

*See Nichiha Warranty for detailed information on terms, conditions and limitations.

*Note: Printed material may not accurately depict actual product color.

©2007 Nichiha USA, Inc. All rights reserved. Printed in the USA. 11/06 PP N1530
NIC060607



Nichiha USA, Inc.
6659 Peachtree Industrial Blvd
Suite AA, Norcross, GA 30092
Toll Free: 1.86 NICHIIHA 1
(866) 424-4421
P. (770) 805-9466
F. (770) 805-9467

www.nichiha.com